




HELIOS LED 8992



HELIOS LED

plastic PC


8991 3000K 8992 4000K



cut out ø 85 mm



EOL LED 8988




EOL LED

plastic PC


8988 3000K 8990 4000K



cut out ø 85 mm



ACRE 10711



ACRE

aluminum, glass


10711




1xGU10, max 15W only LED

IP44/20

cut out ø 75 mm



BAHIA 10712



BAHIA

aluminum, glass

10712




1xGU10, max 15W only LED

IP44/20

cut out ø 75 mm



JULIET 7663



JULIET

steel

7663 7664



1xGU10, max 15W only LED

IP54/20

cut out ø 56 mm



JULIET 7664

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
8991	5W LED	3000K	300 lm	100°	≥ 80	~220-230 V, 50/60 Hz	☐	>0.5	IP44/20	20000h
8992	5W LED	4000K	300 lm	100°	≥ 80	~220-230 V, 50/60 Hz	☐	>0.5	IP44/20	20000h
8988	5W LED	3000K	350 lm	90°	≥ 80	~220-230 V, 50/60 Hz	☐	>0.5	IP44/20	20000h
8990	5W LED	4000K	400 lm	90°	≥ 80	~220-230 V, 50/60 Hz	☐	>0.5	IP44/20	20000h